

PAC Analog PTZ Camera



PAC Analog PTZ Camera

Model	PAC-S3603-IR	PAC-S2801-IR
Camera		
Image Sensor	1/4" SONY EX-View HAD CCD	
Effective Pixel	PAL: 752(H) × 582(V); NTSC: 768(H) × 494(V)	
Video Format	PAL / NTSC	
Resolution	550 TVL	
Min Illumination	Color: 0.1Lux; B/W: 0.01Lux	Color: 0.16Lux; B/W: 0.0015Lux
WB	Auto	
Focus	Auto / Manual	
Exposure Control	Auto / Manual	
S/N Ratio	Not less than 50DB	
BLC	On / Off	
Image Stabilization	On / Off	
WDR	Yes	No
Day/Night	Yes	
Digital Noise Reduction	1~5 Steps / OFF	
D/N ICR	Auto / Manual	
Lens		
Optical Zoom	36X	28X
Digital Zoom	12X	
Focal	f=3.4mm ~ 122.4mm	f=3.5mm ~ 98mm
IRIS	F1.6 ~ F4.5	F1.35 ~ F3.7
View Angle	57.8° (H) ~ 1.7° (V)	55.8° (H) ~ 2.1° (V)
PTZ		
Pan Range	360° Continuous	
Pan Speed	Control Speed: 0.6° ~ 80°/s, Adjustable; Preset Speed: 80°/s	
Tilt Range	-15° ~ 90° (Auto Flip)	
Tilt Speed	Control Speed: 0.3° ~ 70°/s, Adjustable; Preset Speed: 70°/s	
Preset No	256	
Preset Precision	±0.2°	
IR Light		
IR Wave Length	850nm / 940nm	
Range	120m(850nm) / 60m(940nm)	
Switch	Auto / Manual	
General		
Menu Language	English	
Comm Interface	RS-485	
Address	0 ~ 255	
Comm Protocol	PELCO-P / PELCO-D (Self-Adaptive)	
Baud Rate	2400bps, 4800bps, 9600bps, 19200bps (Self-Adaptive)	
Voltage	DC10.8 ~ 28V	
Power	10W (Heater and Lights Off) 20W (Heater On and Lights Off) 30W (Heater and Lights On)	
Working Temperature	-35°C ~ +65°C	
IP Index	IP67	
Other Protection	TVS	
Dimension	Standard: Φ190(mm)×275(mm); With Damper: Φ190(mm)×300(mm)	
Weight	Standard: 4.9kg; Optional: 5.65kg (With Damper)	

Features

- Aluminum PTZ case with high strength;
- IP index up to IP67, full weather proof;
- Powerful aux IR system, range up to 120 meters;
- Hidden seamless window wiper with adjustable speed;
- Built-in defogger;
- New design of drive system, PTZ positioning precision up to +/-0.2°;
- Baud rate, protocol self-adaptive;
- Digital image stabilization (DIS);
- Image flip for stand / ceiling mount;
- Day/night (ICR);
- 10.8~28V voltage input;
- Auto power-off with low power supply.

Dimensions

