

AC3 HD-SDI PTZ Camera




AC3-A2001H-IR


Features

- 1/2.8" CMOS, 2.14MP, 20X optical zoom;
- Supports HD-SDI and Analog output;
- Efficient 60m IR distance;
- Wide dynamic range, ICR day/night;
- Digital image stabilization;
- Protection index: IP66;
- Soft PTZ address, protocol and baud rate self-adaptive;
- 10.8~28V voltage input;
- Auto power-off with low power supply.

Dimensions



Front View



Bottom View

Technical Data

Model Camera	AC3-A2001H-IR
Image Sensor	1/2.8" Progressive Scan CMOS, 2.14MP
Active Pixel	1920(H) x 1080(V)
Signal System (HD)	1080P/30, 1080P/25, 1080I/60, 1080I/50, 720P/60, 720P/50, 720P/30, 720P/25
Signal System (SD)	PAL / NTSC
Min Illumination	Color: 0.5Lux; B/W: 0.1Lux
WB	Auto
Focus	Auto / Manual
Exposure Control	Auto / Manual
S/N Ratio	Not less than 50DB
BLC	On / Off
WDR	On / Off
Digital Noise Reduction	1~5 Steps / OFF
D/N ICR	Auto / Manual
Lens	
Optical Zoom	20X
Digital Zoom	12X
Focal	f=4.7mm ~ 94mm
IRIS	F1.6 ~ F3.5
View Angle	59.5° (H) ~ 2.9° (V)
PTZ	
Pan Range	360° Continuous
Pan Speed	Control Speed: 0.1° ~ 60°/s, adjustable; Preset Speed: 60°/s
Tilt Range	-15° ~ 90° (Auto Flip)
Tilt Speed	Control Speed: 0.2° ~ 60°/s, adjustable; Preset Speed: 60°/s
Preset No	256
Preset Precision	±0.2°
IR Light	
IR Wave Length	850nm
Range	60m
Switch	Auto / Manual
General	
Menu Language	English
Video Output (HD)	HD-SDI
Video Output (SD)	CVBS
Comm Interface	RS-485
Address	0 ~ 255
Comm Protocol	PELCO-P / PELCO-D (Self-Adaptive)
Baud Rate	2400bps, 4800bps, 9600bps, 19200bps (Self-Adaptive)
Voltage	DC10.8 ~ 28V
Power	Min: 9W; Max: 20W
Working Temperature	-25°C ~ +65°C
IP Index	IP66
Dimension	Φ136(mm)×185(mm)
Weight	2.1Kg